MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

Identification of the preparation	11 Series (11S/11L)
Product use	Inkjet printing
Version #	10
Revision date	19-Jan-15
CAS #	Mixture
Company identification	Sojet Electronics(XiaMen) Co.,Ltd.
	Room 402 4/F, Hong Ye Building, Chuang Ye Park,
	Torch Hi-Tech Industrial Development Zone,
	XiaMen, Fujian, China
	Phone No. +86-592-5771357
	Fax No. +86-592-5565048
	E-mail: partner@sojet-tech.com

2. Hazards Identification

Emergency overview	Contact with skin and eyes may result in irritation.
Acute health effects	
	Any potential hazards are presumed to be due to exposure to the components.
Skin contact	2-pyrrolidone Contact with skin may result in irritation.
Eye contact	2-pyrrolidone Contact with eyes may result in irritation.
	Isopropyl Alcohol Contact with eyes may result in severe irritation.
Inhalation	2-pyrrolidone Inhalation may result in respiratory irritation. Isopropyl Alcohol Inhalation may cause drowsiness or dizziness.
Ingestion	2-pyrrolidone Ingestion may result in nausea, vomiting and diarrhea.
Potential health effects	
Routes of exposu	Potential routes of overexposure to this product are skin and eye contact
	Inhalation of vapor and ingestion are not expected to be significant routes of exposure for this product under normal use conditions.
	Complete toxicity data are not available for this specific formulation
Chronic health ef	ffects None known.
Carcinogenicity	Carbon black is classified by the IARC as a Group 2B carcinogen (the substance is possibly carcinogenic to humans). Carbon black in this preparation, due to its bound form, does not present this carcinogenic risk. None of the other ingredients in this preparation are classified as carcinogens according to ACGIH, EU, IARC, MAK, NTP or OSHA.

3. Composition / Informa	ation on Ingradiants		
Components		CAS #	Percent
Water		7732-18-5	< 80
2-pyrrolidone		616-45-5	< 15
Carbon black		1333-86-4	< 5
Isopropyl Alcohol		67-63-0	< 2.5
Composition comments	This ink supply contains an aqueous ink formula This product has been evaluated using criteria s Communication Standard).		0.1200 (Hazard
	Carbon black is present only in a bound form in	this preparation.	
4. First Aid Measures			
First aid procedures			
Eye contact	Do not rub eyes. Immediately flush with large a least 15 minutes or until particles are removed.		
Skin contact	Wash affected areas thoroughly with mild soap attention.	and water. If irritation	persists get medical
Inhalation	Move to fresh air. If symptoms persist, get med	lical attention.	
Ingestion	If ingestion of a large amount does occur, seek	medical attention.	
General advice	No additional information		
5. Fire Fighting Measures	5		
Flammable properties	None known.		
Extinguishing media Suitable extinguishing media	CO2, water, dry chemical, or foam		
Unsuitable extinguishing media	None known.		
Specific methods	None established.		
Hazardous combustion products	Refer to section 10.		
6. Accidental Release Me	asures		
Personal precautions	Wear appropriate personal protective equipmer	nt.	
Environmental precautions	Do not let product enter drains. Do not flush in	to surface water or sar	itary sewer system.
Methods for containment	Dike the spilled material, where this is possible. or diatomaceous earth, commercial sorbents, o		
Methods for cleaning up	Soak up with inert absorbent material.		
Other information	Soak up with inert absorbent material. Slowly v sealed container. Dispose of in compliance with section 13 Disposal considerations.		
7. Handling and Storage			
Handling	Avoid contact with skin, eyes and clothing.		
Storage	Keep out of the reach of children. Keep away fr	rom excessive heat or o	cold.
8. Exposure Controls / Pe	ersonal Protection		
Occupational exposure limits ACGIH			
Components	Туре	Value	Form
Carbon black (1333-86-4) Isopropyl Alcohol (67-63-0)	TWA BEI	3.0000 mg/m3 40.0000 mg/l	Inhalable fraction.
Material name: 11 Series	STEL	400.0000 ppm	MSDS

using the Sustained Combustibility Test (method in US 49CFR173, Appendix H).Evaporation rateNot determinedFlammability limits in air, upper, % by volumeNot available.Flammability limits in air, lower, % by volumeNot available.Vapor pressureNot determinedVapor densityNot available.Specific gravity1Relative densityNot available.Solubility (water)Soluble in waterAuto-ignition temperatureNot available.	Components		Туре	Value Form
Components Type Value Isopropyl Alcohol (67-63-0) PEL 400.0000 ppm 980.0000 mg/m3 U.S Tennessee Components Type Value Carbon black (1333-86-4) Isopropyl Alcohol (67-63-0) TWA 3.5000 mg/m3 TWA 3.5000 mg/m3 1225.0000 mg/m3 TWA 980.0000 ppm 1225.0000 pm 980.0000 ppm 980.0000 ppm 1225.0000 mg/m3 Exposure guidelines Exposure limits have not been established for this product. Engineering controls Use in a well ventilated area. Personal protective equipment considerations Use personal protective equipment to minimize exposure to skin and eye. 9. Physical & Chemical Properties Appearance Not available. Color Black. Odor Odor Not available. Use personal protective equipment to minimize exposure to skin and eye. Physical & Chemical Properties Appearance Not available. Odor Not available. Statustical State Uguid Freezing point Not available. Statustical State Statustical State Boiling point 209 C90 Persky-Martere Goordo Cupi No ignition, sustained combustion or flash			TWA	200.0000 ppm
Components Type Value Isopropyl Alcohol (67-63-0) PEL 400.0000 ppm 980.0000 mg/m3 U.S Tennessee Components Type Value Carbon black (1333-86-4) Isopropyl Alcohol (67-63-0) TWA 3.5000 mg/m3 TWA 3.5000 mg/m3 1225.0000 mg/m3 TWA 980.0000 ppm 1225.0000 pm 980.0000 ppm 980.0000 ppm 1225.0000 mg/m3 Exposure guidelines Exposure limits have not been established for this product. Engineering controls Use in a well ventilated area. Personal protective equipment considerations Use personal protective equipment to minimize exposure to skin and eye. 9. Physical & Chemical Properties Appearance Not available. Color Black. Odor Odor Not available. Use personal protective equipment to minimize exposure to skin and eye. Physical & Chemical Properties Appearance Not available. Odor Not available. Statustical State Uguid Freezing point Not available. Statustical State Statustical State Boiling point 209 C90 Persky-Martere Goordo Cupi No ignition, sustained combustion or flash				
Isoprop/I Alcohol (67-63-0) PEL 400.0000 ppm 980.0000 mg/m3 U.S Tennessee Components Type Value Carbon Black (1333-86-4) Isoprop/I Alcohol (67-63-0) TWA 3.5000 mg/m3 U.S Tennessee 500.0000 ppm 1225.0000 mg/m3 TWA 3.5000 mg/m3 Exposure guidelines Exposure limits have not been established for this product. mg/m3 Engineering controls Use in a well ventilated area. 900.0000 mg/m3 Personal protective equipment General hygiene considerations Handle in accordance with good industrial hygiene and safety practice. General Use personal protective equipment to minimize exposure to skin and eye. 9. 9. Physical & Chemical Properties Appearance Not available. Appearance Color Black. Odor Not available. Odor Not available. Physical state Liquid Freezing point Not available. Physical state Liquid Freezing point Not available. Physical state Liquid Freezing point Not available. Not available. Physical state Liquid Freezing point			Type	Value
U.S Tennessee Type Value Components TWA 3.5000 mg/m3 Exposure Guidelines STEL 500.0000 ppm 1225.0000 mg/m3 TWA 400.0000 ppm 1225.0000 mg/m3 TWA 400.0000 ppm 1225.0000 mg/m3 TWA 400.0000 ppm 1225.0000 mg/m3 Exposure guidelines Exposure limits have not been established for this product. Engineering controls Use in a well ventilated area. Personal protective equipment General hugiene General Use personal protective equipment to minimize exposure to skin and eye. 9. Physical & Chemical Properties Appearance Not available. Color Not available. Odor Not available. Freezing point <t< td=""><td></td><td></td><td></td><td></td></t<>				
Components Type Value Carbon black (1333-86-4) Isopropyl Alcohol (67-63-0) TWA 3.5000 mg/m3 STEL 500.0000 ppm 1225,0000 mg/m3 WA 400.0000 ppm 980.0000 mg/m3 Exposure guidelines Exposure limits have not been established for this product. Exposure guidelines Exposure limits have not been established for this product. Engineering controls Use in a well ventilated area. Personal protective equipment General hygiene considerations Handle in accordance with good industrial hygiene and safety practice. General hygiene considerations Use personal protective equipment to minimize exposure to skin and eye. Physical & Chemical Properties Appearance Not available. Odor Not available. Odor Odor Not available. Odor Not available. Freezing point Freezing point Not available. Souge 32 °C) Frash point 131 °F (55 °C) Pensky-Martens Closed Cup; No ignition, sustained combustion or flashing detecte using the Sustained Combustibility Test (method in US 49CFR173, Appendix H). Evaporation rate Not available. Souge 32 °C) Flash point Not available. Freezing point Not available. Souge 400 chemined Souge 400 chemined Souge 400 ch			PEL	
Components Type Value Carbon black (1333-86-4) Isopropyl Alcohol (67-63-0) TWA 3.5000 mg/m3 STEL 500.0000 ppm 1225,0000 mg/m3 WA 400.0000 ppm 980.0000 mg/m3 Exposure guidelines Exposure limits have not been established for this product. Exposure guidelines Exposure limits have not been established for this product. Engineering controls Use in a well ventilated area. Personal protective equipment General hygiene considerations Handle in accordance with good industrial hygiene and safety practice. General hygiene considerations Use personal protective equipment to minimize exposure to skin and eye. Physical & Chemical Properties Appearance Not available. Odor Not available. Odor Odor Not available. Odor Not available. Freezing point Freezing point Not available. Souge 32 °C) Frash point 131 °F (55 °C) Pensky-Martens Closed Cup; No ignition, sustained combustion or flashing detecte using the Sustained Combustibility Test (method in US 49CFR173, Appendix H). Evaporation rate Not available. Souge 32 °C) Flash point Not available. Freezing point Not available. Souge 400 chemined Souge 400 chemined Souge 400 ch				
Carbon black (1333-86-4) Isopropyl Alcohol (67-63-0) TWA 3.5000 mg/m3 STEL 500.0000 ppm 12225.000 mg/m3 TWA 400.0000 ppm 980.0000 mg/m3 Exposure guidelines Exposure limits have not been established for this product. Engineering controls Use in a well ventilated area. Personal protective equipment General hygiene considerations Handle in accordance with good industrial hygiene and safety practice. General Use personal protective equipment to minimize exposure to skin and eye. 9. Physical & Chemical Properties Appearance Not available. Color Black. Odor Not available. Freezing point Not available. Physical state Liquid Form Not available. Pil 7.8 Melting point Not available. Freezing point Not available. Evaporation rate Not available. Freezing point Not available. Freezing point Not available. Freezing point Not available. Evaporation rate Not determined Not available. Statined Combustibility Test (method in US 49CFR173, Appendi				
Isopropyl Alcohol (67-63-0) STEL 500.0000 ppm 1225.0000 mg/m3 TWA 400.0000 ppm 980.0000 mg/m3 Exposure guidelines Exposure limits have not been established for this product. Engineering controls Use in a well ventilated area. Personal protective equipment considerations Handle in accordance with good industrial hygiene and safety practice. General hygiene considerations Handle in accordance with good industrial hygiene and safety practice. General hygiene considerations Not available. Odor Not available. Color Black. Odor Not available. Color Not available. Odor Not available. Freezing point Not available. Physical state Liquid Freezing point Not available. Boiling point 200 °F (93.3 °C) Flash point Not available. Freezing point Not available. Boiling point 200 °F (93.3 °C) Flash point Not available. Freezing point Not available. Syper yessure Not available. Hormability limits in air, lower, % by volume				
1225.0000 mg/m3 TWA 400.0000 ppm 980.0000 mg/m3 Exposure guidelines Exposure limits have not been established for this product. Engineering controls Use in a well ventilated area. Personal protective equipment General Nugeine General Nugeine Handle in accordance with good industrial hygiene and safety practice. Onsiderations General Nugeine 9. Physical & Chemical Properties Appearance Appearance Not available. Color Black. Odor Not available. Physical state Liquid Form Not available. Pit 7.8 Melting point Not available. Freezing point Not available. Form Not available. Freezing point Not available. Freezing point Not available. Freezing point Not available. Freezing volume Sustained Combustion or flashing detecte using the Sustained Combustibility Test (method in US 49CFR173, Appendix H). Evaporation rate Not determined Flammability limits in air, pot available.				
TWA mg/m3 400.0000 pm 980.0000 mg/m3 Exposure guidelines Exposure limits have not been established for this product. Engineering controls Use in a well ventilated area. Personal protective equipment considerations Handle in accordance with good industrial hygiene and safety practice. General hygiene Handle in accordance with good industrial hygiene and safety practice. Or providerations Use personal protective equipment to minimize exosure to skin and eye. 9. Physical & Chemical Proverties Not available. Color Black. Odor Not available. Odor Not available. Odor Not available. Physical state Liquid Freezing point Not available. Solubling point 200 °F (93.3 °C) Flash point 200 °F (93.3 °C) Flash point 200 °F (93.3 °C) Flash point Not available. Plammability limits in air, upper, % by volume Not available. Flammability limits in air, upper, % by volume Not available. Flammability limits in air, upper, % by volume Not available. Flammability limits in air, upper, % by volume Not available. Specific gravity 1 Relative density Not available. Specific gravity 1 <td>Isopropyi Aiconoi (67-63-0)</td> <td></td> <td>STEL</td> <td></td>	Isopropyi Aiconoi (67-63-0)		STEL	
980.0000 mg/m3 Exposure guidelines Exposure limits have not been established for this product. Engineering controls Use in a well ventilated area. Personal protective equipment Handle in accordance with good industrial hygiene and safety practice. Considerations General hygiene General Use personal protective equipment to minimize exposure to skin and eye. 9. Physical & Chemical Properties Appearance Not available. Color Black. Odor Not available. Odor Not available. Physical state Liquid Form Not available. Physical state Liquid Foregrap point Not available. Physical state Liquid Foregrap point Not available. Boiling point 200 °F (93.3 °C) Flammability limits in air, upper, % by volume Not available. Flammability limits in air, upper, % by volume Not available. Flammability limits in air, upper, % by volume Not available. Specific gravity 1 Relative density Not				
Exposure guidelines Exposure limits have not been established for this product. Engineering controls Use in a well ventilated area. Personal protective equipment General hygiene General Use personal protective equipment to minimize exposure to skin and eye. 9. Physical & Chemical Properties Appearance Not available. Color Black. Odor Not available. Color Not available. Odor Not available. Physical state Liquid Form Not available. PiH 7.8 Melting point Not available. Boiling point 200 °F (93.3 °C) Flash point 131 °F (55 °C) Pensky-Martens Closed Cup; No ignition, sustained combustion or flashing detecter using the Sustained Combustibility Test (method in US 49CFR173, Appendix H). Evaporation rate Not available. Flammability limits in air, upper volume Not available. Plaropersure Not determined Vapor pressure Not determined Vapor density Not available. Specific gravity 1 Relative density Not			TWA	400.0000 ppm
Engineering controls Use in a well ventilated area. Personal protective equipment considerations Handle in accordance with good industrial hygiene and safety practice. General Use personal protective equipment to minimize exposure to skin and eye. 9. Physical & Chemical Properties Appearance Not available. Color Black. Odor Not available. Odor Not available. Physical state Liquid Form Not available. Pdeling point Not available. Freezing point Not available. Priezing point Not available. Freezing point Not available. Freezing point Not available. Evaporation rate Not available. Flammability limits in air, upper, % by volume Not available. Flammability limits in air, point Not available. Flammability limits in air, por pressure Not available. Vapor pressure Not available. Vapor pressure Not determined Vapor density Not available. Specific gravity 1 Relative density Not availabl				980.0000 mg/m3
Engineering controls Use in a well ventilated area. Personal protective equipment considerations Handle in accordance with good industrial hygiene and safety practice. General Use personal protective equipment to minimize exposure to skin and eye. 9. Physical & Chemical Properties Appearance Not available. Color Black. Odor Not available. Odor Not available. Physical state Liquid Form Not available. Pdeling point Not available. Freezing point Not available. Priezing point Not available. Freezing point Not available. Freezing point Not available. Evaporation rate Not available. Flammability limits in air, upper, % by volume Not available. Flammability limits in air, point Not available. Flammability limits in air, por pressure Not available. Vapor pressure Not available. Vapor pressure Not determined Vapor density Not available. Specific gravity 1 Relative density Not availabl	Exposure guidelines	Exposure limits have	not been establishe	d for this product.
Personal protective equipment General hygiene considerations Handle in accordance with good industrial hygiene and safety practice. General Use personal protective equipment to minimize exposure to skin and eye. 9. Physical & Chemical Properties Appearance Not available. Color Black. Odor Not available. Odor Not available. Odor Not available. Physical state Liquid Form Not available. Prisonal point Not available. Pif 7.8 Melting point Not available. Boiling point Not available. Boiling point Not available. Freezing point Not available. Boiling point Not available. Evaporation rate Not determined Flasmability limits in air, upper, % by volume Not available. Flammability limits in air, lower, % by volume Not available. Vapor density Not available. Vapor density Not available. Specific gravity 1 Relative density<		-		
General hygiene considerations GeneralHandle in accordance with good industrial hygiene and safety practice.9. Physical & Chemical PropertiesAppearanceNot available.ColorBlack.OdorNot available.OdorNot available.OdorNot available.OdorNot available.Physical stateLiquidFormNot available.Ph7.8Melting pointNot available.Boiling point200 °F (93.3 °C)Flash point131 °F (55 °C) Pensky-Martens Closed Cup; No ignition, sustained combustion or flashing detecte using the Sustained Combustibility Test (method in US 49CFR173, Appendix H).Evaporation rateNot available.Flammability limits in air, lower, % by volumeNot available.Vapor gressureNot determinedSpecific gravity1Relative densityNot available.Solubility (water)Soluble in waterAuto-ignition temperatureNot available.				
General Use personal protective equipment to minimize exposure to skin and eye. 9. Physical & Chemical Properties Appearance Not available. Color Black. Odor Not available. Odor Not available. Odor Not available. Odor Not available. Physical state Liquid Form Not available. PH 7.8 Melting point Not available. Breiling point Not available. Breiling point 200 °F (93.3 °C) Flash point 131 °F (55 °C) Pensky-Martens Closed Cup; No ignition, sustained combustion or flashing detecte using the Sustained Combustibility Test (method in US 49CFR173, Appendix H). Evaporation rate Not available. Flammability limits in air, upper, % by volume Not available. Vapor pressure Not determined Flammability limits in air, low available. Not available. Vapor density Not available. Specific gravity 1 Relative density Not available. Solubility (water) Soluble in water Auto-ignition temperature Not av	General hygiene		e with good industria	l hygiene and safety practice.
9. Physical & Chemical Properties Appearance Not available. Color Black. Odor Not available. Odor Not available. Odor threshold Not available. Physical state Liquid Form Not available. PH 7.8 Melting point Not available. Boiling point 200 °F (93.3 °C) Flash point 131 °F (55 °C) Pensky-Martens Closed Cup; No ignition, sustained combustion or flashing detecte using the Sustained Combustibility Test (method in US 49CFR173, Appendix H). Evaporation rate Not available. Flammability limits in air, upper, % by volume Not available. Flammability limits in air, upper, % by volume Not available. Vapor pressure Not determined Vapor gressure Not determined Vapor density Not available. Specific gravity 1 Relative density Not available. Solubility (water) Soluble in water Auto-ignition temperature Not available.		Use personal protect	ive equipment to mir	nimize exposure to skin and eye.
AppearanceNot available.ColorBlack.OdorNot available.Odor thresholdNot available.Physical stateLiquidFormNot available.pH7.8Melting pointNot available.Freezing pointNot available.Boiling point200 °F (93.3 °C)Flash point131 °F (55 °C) Pensky-Martens Closed Cup; No ignition, sustained combustion or flashing detecte using the Sustained Combustibility Test (method in US 49CFR173, Appendix H).Evaporation rateNot available.Flammability limits in air, upper, % by volumeNot available.Flammability limits in air, upper, % by volumeNot available.Specific gravity1Relative densityNot available.Specific gravity1Relative densitySoluble in waterAuto-ignition temperatureNot available.Solublity (water)Soluble in water				
ColorBlack.OdorNot available.Odor thresholdNot available.Physical stateLiquidFormNot available.pH7.8Melting pointNot available.Freezing pointNot available.Boiling point200 °F (93.3 °C)Flash point131 °F (55 °C) Pensky-Martens Closed Cup; No ignition, sustained combustion or flashing detecte using the Sustained Combustibility Test (method in US 49CFR173, Appendix H).Evaporation rateNot available.Flammability limits in air, upper, % by volumeNot available.Flammability limits in air, upper, % by volumeNot available.Specific gravity1Relative densityNot available.Specific gravity1Relative densityNot available.Solubli Ity (water)Soluble in waterAuto-ignition temperatureNot available.	•	•		
OdorNot available.Odor thresholdNot available.Physical stateLiquidFormNot available.pH7.8Melting pointNot available.Freezing pointNot available.Boiling point200 °F (93.3 °C)Flash point31 °F (55 °C) Pensky-Martens Closed Cup; No ignition, sustained combustion or flashing detecte using the Sustained Combustibility Test (method in US 49CFR173, Appendix H).Evaporation rateNot available.Flammability limits in air, upper, % by volumeNot available.Flammability limits in air, lower, % by volumeNot available.Vapor pressureNot determinedVapor densityNot available.Specific gravity1Relative densityNot available.Solubility (water)Soluble in waterAuto-ignition temperatureNot available.				
OdorNot available.Physical stateLiquidFormNot available.pH7.8Melting pointNot available.Freezing pointNot available.Boiling point200 °F (93.3 °C)Flash point131 °F (55 °C) Pensky-Martens Closed Cup; No ignition, sustained combustion or flashing detecte using the Sustained Combustibility Test (method in US 49CFR173, Appendix H).Evaporation rateNot available.Flammability limits in air, lower, % by volumeNot available.Flammability limits in air, lower, % by volumeNot available.Vapor pressureNot determinedVapor densityNot available.Specific gravity1Relative densityNot available.Solubility (water)Soluble in waterAuto-ignition temperatureNot available.				
Physical stateLiquidFormNot available.pH7.8Melting pointNot available.Freezing pointNot available.Boiling point200 °F (93.3 °C)Flash point131 °F (55 °C) Pensky-Martens Closed Cup; No ignition, sustained combustion or flashing detecte using the Sustained Combustibility Test (method in US 49CFR173, Appendix H).Evaporation rateNot available.Flammability limits in air, upper, % by volumeNot available.Flammability limits in air, lower, % by volumeNot available.Vapor pressureNot determinedVapor pressureNot determinedSpecific gravity1Relative densityNot available.Solublity (water)Soluble in waterAuto-ignition temperatureNot available.				
FormNot available.pH7.8Melting pointNot available.Freezing pointNot available.Boiling point200 °F (93.3 °C)Flash point131 °F (55 °C) Pensky-Martens Closed Cup; No ignition, sustained combustion or flashing detecte using the Sustained Combustibility Test (method in US 49CFR173, Appendix H).Evaporation rateNot determinedFlammability limits in air, upper, % by volumeNot available.Flammability limits in air, lower, % by volumeNot available.Vapor pressureNot determinedVapor densityNot available.Specific gravity1Relative densityNot available.Solublity (water)Soluble in waterAuto-ignition temperatureNot available.				
pH7.8Melting pointNot available.Freezing pointNot available.Boiling point200 °F (93.3 °C)Flash point131 °F (55 °C) Pensky-Martens Closed Cup; No ignition, sustained combustion or flashing detecte using the Sustained Combustibility Test (method in US 49CFR173, Appendix H).Evaporation rateNot determinedFlammability limits in air, upper, % by volumeNot available.Flammability limits in air, lower, % by volumeNot available.Vapor pressureNot determinedSpecific gravity1Relative densityNot available.Solublity (water)Soluble in waterAuto-ignition temperatureNot available.	-	•		
Melting pointNot available.Freezing pointNot available.Boiling point200 °F (93.3 °C)Flash point131 °F (55 °C) Pensky-Martens Closed Cup; No ignition, sustained combustion or flashing detecte using the Sustained Combustibility Test (method in US 49CFR173, Appendix H).Evaporation rateNot determinedFlammability limits in air, upper, % by volumeNot available.Flammability limits in air, lower, % by volumeNot available.Vapor pressureNot determinedSpecific gravity1Relative densityNot available.Solubility (water)Soluble in waterAuto-ignition temperatureNot available.				
Freezing pointNot available.Boiling point200 °F (93.3 °C)Flash point131 °F (55 °C) Pensky-Martens Closed Cup; No ignition, sustained combustion or flashing detecte using the Sustained Combustibility Test (method in US 49CFR173, Appendix H).Evaporation rateNot determinedFlammability limits in air, upper, % by volumeNot available.Flammability limits in air, lower, % by volumeNot available.Vapor pressureNot determinedVapor densityNot available.Specific gravity1Relative densityNot available.Solubility (water)Soluble in waterAuto-ignition temperatureNot available.	1	-		
Boiling point200 °F (93.3 °C)Flash point131 °F (55 °C) Pensky-Martens Closed Cup; No ignition, sustained combustion or flashing detecte using the Sustained Combustibility Test (method in US 49CFR173, Appendix H).Evaporation rateNot determinedFlammability limits in air, upper, % by volumeNot available.Flammability limits in air, lower, % by volumeNot available.Vapor pressureNot determinedVapor densityNot available.Specific gravity1Relative densityNot available.Solubility (water)Soluble in waterAuto-ignition temperatureNot available.				
Flash point131 °F (55 °C) Pensky-Martens Closed Cup; No ignition, sustained combustion or flashing detecte using the Sustained Combustibility Test (method in US 49CFR173, Appendix H).Evaporation rateNot determinedFlammability limits in air, upper, % by volumeNot available.Flammability limits in air, lower, % by volumeNot available.Vapor pressureNot determinedVapor densityNot available.Specific gravity1Relative densityNot available.Solubility (water)Soluble in waterAuto-ignition temperatureNot available.				
Evaporation rateNot determinedFlammability limits in air, upper, % by volumeNot available.Flammability limits in air, lower, % by volumeNot available.Vapor pressureNot determinedVapor densityNot available.Specific gravity1Relative densityNot available.Solubility (water)Soluble in waterAuto-ignition temperatureNot available.	Flash point	131 °F (55 °C) Pensl		
Flammability limits in air, upper, % by volumeNot available.Flammability limits in air, lower, % by volumeNot available.Vapor pressureNot determinedVapor densityNot available.Specific gravity1Relative densityNot available.Solubility (water)Soluble in waterAuto-ignition temperatureNot available.			Compustibility Test (I	method in US 49CFR173, Appendix H).
upper, % by volumeNot available.Flammability limits in air, lower, % by volumeNot available.Vapor pressureNot determinedVapor densityNot available.Specific gravity1Relative densityNot available.Solubility (water)Soluble in waterAuto-ignition temperatureNot available.	•			
Iower, % by volumeVapor pressureNot determinedVapor densityNot available.Specific gravity1Relative densityNot available.Solubility (water)Soluble in waterAuto-ignition temperatureNot available.	upper, % by volume	not avaliable.		
Vapor densityNot available.Specific gravity1Relative densityNot available.Solubility (water)Soluble in waterAuto-ignition temperatureNot available.	Flammability limits in air, lower, % by volume	Not available.		
Specific gravity1Relative densityNot available.Solubility (water)Soluble in waterAuto-ignition temperatureNot available.	Vapor pressure	Not determined		
Relative densityNot available.Solubility (water)Soluble in waterAuto-ignition temperatureNot available.	Vapor density	Not available.		
Solubility (water)Soluble in waterAuto-ignition temperatureNot available.	Specific gravity	1		
Auto-ignition temperature Not available.	Relative density	Not available.		
Auto-ignition temperature Not available.	Solubility (water)	Soluble in water		
	Auto-ignition temperature	Not available.		
	Decomposition temperature	Not available.		

Viscosity	2 ср		
Bulk density	1 gm/ml		
VOC	Not available.		
Other information	For other VOC regulatory data	/information see section 15	
10. Chemical Stability & I	•		
Chemical stability	Stable under recommended sto	-	
Incompatible materials	Incompatible with strong base		
Hazardous decomposition products	Upon decomposition, this product may yield gaseous nitrogen oxides, carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.		
Possibility of hazardous reactions	Will not occur.		
11. Toxicological Informa	ation		
Carcinogenicity	2B) and by the State of Ca both organizations indicate	as a carcinogen by the IARC (possibly carcinogenic to humans, Group alifornia under Proposition 65. In their evaluations of carbon black, e that exposure to carbon black, per se, does not occur when it oduct matrix, specifically, rubber, ink, or paint.	
ACGIH Carcinogens			
Carbon black (CAS 1333-8	-	A3 Confirmed animal carcinogen with unknown relevance to humans.	
Isopropyl Alcohol (CAS 67 IARC Monographs. Overall	'-63-0) Evaluation of Carcinogenicit	A4 Not classifiable as a human carcinogen. Y	
Carbon black (CAS 1333-8		2B Possibly carcinogenic to humans.	
	ce of carcinogenicity in huma		
Carbon black (CAS 1333-& Serious eye damage/eye	Not available.	Inadequate data.	
irritation			
Symptoms and target organs			
Target Organs (NIOSH)		5 m	
Carbon black (CAS 1333-8	30-4)	Eyes Respiratory system	
Isopropyl Alcohol (CAS 67	7-63-0)	Eyes Respiratory system Skin	
Further information		available for this specific formulation. I health effects and Section 4 for first aid measures.	
12. Ecological Informatio	n		
Aquatic toxicity	LC50/96h/Fathead minnows =	>750 mg/L	
Persistence and degradability	Not available.		
Partition coefficient	Not determined		
13. Disposal Consideration	ns		
Disposal instructions		rain into sewers/water supplies.	
Disposal instructions		ording to Local, State, Federal, and Provincial Environmental	
	recycling of Sojet original inkje	lemark) supplies recycling program enables simple, convenient et and LaserJet supplies. For more information and to determine if location, please visit http://www.sojet-tech.com.	
14. Transport Informatio	n		
Further information	prescribed in the UN Manual o Goods Regulations Section 3.3	ion, or flashing detected, using the Sustained Combustibility Test f Tests and Criteria, Part III subsection 32.5.2. Refer to Dangerous	
Material name: 11 Series	(method in US CFR173, Appen		
	19-1an-2015 Print date: 20-1an-2		

Sojet Electronics(XiaMen) Co.,Ltd.

DOT	
Not regulated as dangerous goods	
ΙΑΤΑ	
Not regulated as dangerous goods	
IMDG	
Not regulated as dangerous goods	
RID	
Not regulated as dangerous goods	Ъ.
15. Regulatory Informati	on
US federal regulations	US TSCA 12(b): Does not contain listed chemicals.
CERCLA (Superfund) reportabl	
None	
Occupational Safety and Healt 29 CFR 1910.1200 hazardous chemical	h Administration (OSHA) Yes
Superfund Amendments and R	Reauthorization Act of 1986 (SARA)
Hazard categories	Immediate Hazard - No Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No
Section 302 extremely hazardous substance	No
Section 311 hazardous chemical	No
State regulations	
US - Pennsylvania RTK - H	lazardous Substances: Listed substance
2-pyrrolidone (CAS 616-4	-5-5) Listed.
Carbon black (CAS 1333- Isopropyl Alcohol (CAS 67	
Regulatory information	All chemical substances have been notified or are exempt from notification under chemical substances notification laws in the following countries: US (TSCA), EU (EINECS/ELINCS), Switzerland, Canada (DSL/NDSL), Australia, Japan, Philippines, South Korea, New Zealand, and China.
Other information	Specific Provisions: Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC (in the amended version OJ L 396 from 29.05.2007 page 3 with further rectifications and amendments). Exposure Limits (See Section 8): Executive regulation of Minister of Labour and Social Policy dated Nov. 29, 2002 concerning the highest exposure limits and volume of factors harmful for health and environment at work (Official Journal of Laws no 217/2002 item 1833 with further amendments).
16. Other Information	
Other information	This MSDS was prepared in accordance with USA OSHA Hazard Communications regulation (29 CFR 1910.1200).
HMIS® ratings	Health: 1 Flammability: 2 Physical hazard: 0
NFPA ratings	Health: 1 Flammability: 2 Instability: 0

Disclaimer	This Safety Data Sheet document is provided without charge to customers of Sojet Company. Data is the most current known to Sojet Company at the time of preparation of this document and is believed to be accurate. It should not be construed as guaranteeing specific properties of the products as described or suitability for a particular application. This document was prepared to the requirements of the jurisdiction specified in Section 1 above and may not meet regulatory requirements in other countries.
Issue date	11-Mar-2013
This data sheet contains changes from the previous version in section(s):	Product and Company Identification: Alternate Trade Names
Manufacturer information	XiaMen Sojet Electronics Co.,Ltd.
	Room 402 4/F, Hong Ye Building, Chuang Ye Park,
	Torch Hi-Tech Industrial Development Zone,
	XiaMen, Fujian, China
	Phone No. +86-592-5771357 Fax No. +86-592-5565048
	E-mail: partner@sojet-tech.com

Explanation of abbreviations

ACGIH	American Conference of Governmental Industrial Hygienists
CAS	Chemical Abstracts Service
CERCLA	Comprehensive Environmental Response Compensation and Liability Act
CFR	Code of Federal Regulations
COC	Cleveland Open Cup
DOT	Department of Transportation
EPCRA	Emergency Planning and Community Right-to-Know Act (aka SARA)
IARC	International Agency for Research on Cancer
NIOSH	National Institute for Occupational Safety and Health
NTP	National Toxicology Program
OSHA	Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
RCRA	Resource Conservation and Recovery Act
REC	Recommended
REL	Recommended Exposure Limit
SARA	Superfund Amendments and Reauthorization Act of 1986
STEL	Short-Term Exposure Limit
TCLP	Toxicity Characteristics Leaching Procedure
TLV	Threshold Limit Value
TSCA	Toxic Substances Control Act
VOC	Volatile Organic Compounds